

GEARBOX WITH DUAL COAXIAL INPUT SHAFTS, CENTRAL DIFFERENTIAL 50%-50% TORQUE DISTRIBUTION, ONE OUTPUT SHAFT










ESEMPIO APPLICAZIONE



DIMENSIONS AND WEIGHT

- 1100x1000x1000 mm - Mass = 2300 kg

EXAMPLE TECHNICAL FEATURES

- Ratio i = 1.7/1
- Input power P01 = 750 kW
- Input power P02 = 750 kW
- Output power P03 = 1500 kW
- Input rpm n01 = 1000 rpm
- Input rpm n02 = 1000 rpm
- Output rpm n03 = 1700 rpm
- Input torque Mt01 = 7160 Nm
- Input torque Mt02 = 7160 Nm
- Output torque Mt03 = 8425 Nm

CONSTRUCTION FEATURES

- Power, ratio, torque, rpm, rotation shaft, input and output torque are customizables on request;
- Input and output interface flanges are customizable on request;
- Bearings and gear lubrification are independents;
- Input torque distribution 50% - 50%;
- Working quietness;
- Bearing monitoring with thermal probe on request.

STUDIO TECNICO ZOCCA S.r.l.
Via Andrea Costa, 27 - 40013 Castel Maggiore (BO) - Italy - tel. +39 051 70.01.91
info@studiozocca.com – www.studiozocca.com